

## MINI TORQUE WRENCH

### GS-SERIES

1 ~ 40 Nm

NovaTork offers a complete range of click torque wrenches. These are intended for mounting bolted connections. The GS series are very compact and therefore very lightweight.

This series is available with a fixed ratchet head or a wide variety of insert tools.

The torque is accurately adjustable, whereby the setting ring cannot be twisted unintentionally.

#### FEATURES

- Accuracy:  $\pm 4\%$  in clockwise direction.
- Small sizes and light weight, and can be operated in confined spaces.
- Permanently stamped major and minor scales for precision torque values setting.
- Minor scale is 1/10 of increment of main scale
- Grooved non-slip grip fits comfortably in your hand.
- Various fittings for different applications:
  - GSMH model: Head holder for standard 9x12mm rectangular shank heads.



#### GSMH Model

Type	Insert tool mm	Torque Nm	Weight kg	Width mm	Length mm
<b>GSMH95S</b>	9 x 12	1 ~ 5	0,28	28	170
<b>GSMH915S</b>	9 x 12	3 ~ 25	0,31	28	194
<b>GSMH925S</b>	9 x 12	5 ~ 25	0,33	28	217
<b>GSMH940S</b>	9 x 12	8 ~ 40	1,2	28	244



#### GSM Model


Type	Square Drive	Torque Nm	Weight kg	Width mm	Length mm
<b>GSM15S</b>	1/4"	1 ~ 5	0,30	28	183
<b>GSM115S</b>	1/4"	3 ~ 15	0,33	28	207
<b>GSM125S</b>	1/4"	5 ~ 25	0,35	28	230
<b>GSM240S</b>	3/8"	8 ~ 40	0,37	36	260

#### Torque Locking




1

Pull and hold the locking ring



2

Rotate the tube to adjust the torque by the other hand



3

Release the locking ring after torque being set

#### Optional fittings OH, DH, QH



\* These types of fittings are available on request.