

## TORQUE WRENCH WITH QUICK RELEASE

### BQ-SERIES

### 1 ~ 2000 Nm

NovaTork offers a complete range of click torque wrenches. These are intended for mounting bolted connections. The BQ series are very compact and therefore very lightweight. This series is available with a fixed ratchet head or a wide variety of insert tools. The torque is accurately adjustable, whereby the setting ring cannot be twisted unintentionally.

#### FEATURES

- Accuracy is  $\pm 4\%$  from 20-100% of capacity
- All metal structure, alloy steel pipe, durable
- Clear scale, easy to read
- Minor scale is 1/10 of increment of main scale
- Pull to unlock lock ring keeps selected torque secure from accidental change
- Quick release head
- Grooved non-slip grip



#### BQLM-QR Model

Reversible Ratchet Head Mini

Type	Square Drive	Torque Nm	Length mm	Width mm	Weight kg
<b>BQLSM15-QR</b>	1/4"	1,0 ~ 5,0	217	28	0,3
<b>BQLSM110-QR</b>	1/4"	2,0 ~ 10	227	28	0,32
<b>BQLSM125-QR</b>	1/4"	5,0 ~ 25	265	28	0,33
<b>BQLSM225-QR</b>	3/8"	5,0 ~ 25	265	28	0,35

Reversible Ratchet Head

Type	Square Drive	Torque Nm	Length mm	Width mm	Weight kg
<b>BQLM260-QR</b>	3/8"	10 ~ 60	389	33	0,94
<b>BQLM360-QR</b>	1/2"	10 ~ 60	389	33	0,94
<b>BQLM2100-QR</b>	3/8"	20 ~ 100	428	33	1,04
<b>BQLM3100-QR</b>	1/2"	20 ~ 100	428	33	1,04
<b>BQLM3150-QR</b>	1/2"	30 ~ 150	466	40	1,05
<b>BQLM3220-QR</b>	1/2"	40 ~ 220	507	40	1,16
<b>BQLM3350-QR</b>	1/2"	70 ~ 350	567	40	1,34
<b>BQLM3400-QR</b>	1/2"	80 ~ 400	620	40	1,36
<b>BQLM4600*</b>	3/4"	100 ~ 600	1060	64	5,1
<b>BQLM4800*</b>	3/4"	150 ~ 800	1250	64	5,9
<b>BQLM51000*</b>	1"	200 ~ 1000	1250	71	7
<b>BQLM51500E*</b>	1"	300 ~ 1500	1870	71	10,5
<b>BQLM52000E*</b>	1"	400 ~ 2000	1870	71	10,5

\* Non-Quick Release



#### BMH-QR Model

Rectangular Shank Head Holder Mini

Type	Insert tool mm	Torque Nm	Length mm	Width mm	Weight kg
<b>BMH95S-QR</b>	9 x 12	1,0 ~ 5,0	200	22	0,32
<b>BMH910S-QR</b>	9 x 12	2,0 ~ 10	210	22	0,33
<b>BMH925S-QR</b>	9 x 12	5,0 ~ 25	248	22	0,35

Rectangular Shank Head Holder

Type	Insert tool mm	Torque Nm	Length mm	Width mm	Weight kg
<b>BMH960-QR</b>	9 x 12	10 ~ 60	390,5	22	0,96
<b>BMH9100-QR</b>	9 x 12	20 ~ 100	445,5	22	1,04
<b>BMH14150-QR</b>	14 x 18	30 ~ 150	453,3	32	1,05
<b>BMH14220-QR</b>	14 x 18	40 ~ 220	474,3	32	1,16
<b>BMH14350-QR</b>	14 x 18	70 ~ 350	537,3	32	1,34
<b>BMH14400-QR</b>	14 x 18	80 ~ 400	593,3	32	1,36

#### Optional fittings OH, DH, QH



\* These types of fittings are available on request