

TORQUE WRENCH

GM-SERIES

2,5 ~ 3000 Nm

NovaTork offers a complete range of click torque wrenches. These are intended for mounting bolted connections. The GM series are very compact and therefore very lightweight.

This series is available with a fixed ratchet head or a wide variety of insert tools.

The torque is accurately adjustable, whereby the setting ring cannot be twisted unintentionally.

FEATURES

- Accuracy: $\pm 4\%$ in clockwise direction.
- All steel construction, superb durability.
- Permanently stamped major and minor scales for precision torque values setting.
- Ergonomic non-slip handle.
- Various fittings for different applications:
 - GSMH model: Head holder for 9x12, 14x18, 24x32 of 27x36mm rectangular shank heads.
 - GM-model: Reversible ratchet head with 8° swing, suitable for confined space applications.



GMH Model

Type	Insert tool mm	Torque Nm	Weight kg	Width mm	Length mm
GMH912	9 x 12	2,5 ~ 12	0,58	38	284
GMH920	9 x 12	4 ~ 20	0,58	38	284
GMH930	9 x 12	6 ~ 30	0,72	38	303
GMH960	9 x 12	10 ~ 60	0,86	38	372
GMH9125	9 x 12	25 ~ 125	0,94	38	427
GMH14200	14 x 18	40 ~ 200	1,06	38	459
GMH14335	14 x 18	65 ~ 335	1,2	38	514
GMH14400	14 x 18	80 ~ 400	2,1	38	697
GMH24500	24 x 32	100 ~ 500	5	56	855
GMH24800	24 x 32	160 ~ 800	5,9	56	1055
GMH241000	24 x 32	200 ~ 1000	5,9	56	1055
GMH271500	27 x 36	300 ~ 1500	9	64	1249
GMH272000	27 x 36	400 ~ 2000	9	64	1249
GMH272000E	27 x 36	400 ~ 2000	12,5	64	2200
GMH273000	27 x 36	600 ~ 3000	10,3	64	1249
GMH273000E	27 x 36	600 ~ 3000	15,3	64	2780



GM Model

Type	Square Drive	Torque Nm	Weight kg	Width mm	Length mm
GM112	1/2"	40 ~ 200	1,16	40	468
GSM3335	1/2"	65 ~ 335	1,3	40	528
GSM4800	3/4"	160 ~ 800	5,9	60	1055
GSM53000E	1"	600 ~ 3000	15,5	75	2780

Optional fittings OH, DH, QH



* These types of fittings are available on request.

Torque Locking




1

Pull and hold the locking ring



2

Rotate the tube to adjust the torque by the other hand



3

Release the locking ring after torque being set