

## CLICK TORQUE WRENCH

### STM-SERIES

20 ~ 2000 Nm

NovaTork offers a complete range of click torque wrenches. These are designed for mounting bolted connections. The STM series is of industrial quality and has a very high repeat accuracy.

This series is available with a fixed ratchet head or a wide variety of insert tools. The torque is accurately adjustable on a clearly readable scale. In addition, the blocking feature ensures that the torque cannot be twisted unintentionally.

#### FEATURES

- Unique window scale with fine increments.
- Accuracy is  $\pm 4\%$  of the reading value.
- Ergonomic, non-slip handle.
- Handgrip in engineering plastic, oil resistant and non-slip resistant, durable.
- Push/Pull end cap to secure the set torque value from accidental change.
- This wrench is longer than normal torque wrench, more efficiently while long time using.
- Various fittings for different applications:
  - STMH model: Head holder, for 9x12 or 14x18mm rectangular shank heads.
  - STMX model: Push-through ratchet head for clockwise and counter-clockwise operation.
  - STM model: Compact reversible ratchet head for clockwise and counter-clockwise operation.

#### Optional fittings OH, DH, QH



\* These types of fittings are available on request.



#### STMH Model

Type	Insert tool mm	Torque Nm	Weight kg	Width mm	Length mm
STMH9100	9 x 12	20 ~ 100	0,9	43	423
STMH9150	9 x 12	30 ~ 150	1,1	43	463
STMH14150	14 x 18	30 ~ 150	1,1	43	467
STMH14200	14 x 18	40 ~ 200	1,2	43	494
STMH14300	14 x 18	60 ~ 300	1,2	43	554
STMH14400	14 x 18	80 ~ 400	1,6	56	707



#### STMX Model

Type	Square Drive	Torque Nm	Weight kg	Width mm	Length mm
STMX3100	1/2"	20 ~ 100	1,1	48	438
STMX3200	1/2"	40 ~ 200	1,3	48	505
STMX3300	1/2"	60 ~ 300	1,4	48	565
STMX3400	1/2"	80 ~ 400	1,99	50	700
STMX41000	3/4"	200 ~ 1000	4,55	70	1210
STMX51500	1"	300 ~ 1500	6,5	90	1710
STMX52000	1"	400 ~ 2000	6,8	90	1943



#### STM Model

Type	Square Drive	Torque Nm	Weight kg	Width mm	Length mm
STM125	1/4"	5 ~ 25	0,82	30	321
STM250	3/8"	10 ~ 50	1	38	387
STM3100	1/2"	20 ~ 100	1,1	40	433
STM3200	1/2"	40 ~ 200	1,25	40	491
STM3300	1/2"	60 ~ 300	1,4	40	551
STM3340	1/2"	68 ~ 340	1,4	40	551
STM3400	1/2"	80 ~ 400	1,97	40	700
STM41000	3/4"	200 ~ 1000	4,2	60	1105
STM51500	1"	300 ~ 1500	6,5	90	1710