

ASSEMBLY TOOLS CORDLESS

PRODUCTIVITY, FLEXIBILITY & ACCURACY

Red Rooster cordless assembly tools with automatic shut-off are very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains.

RRI-BA SERIES
Torque: 3 - 90 Nm



RRI-BS SERIES
Torque: 0,8 - 12 Nm



RRI-BIM SERIES
Torque: 7 - 65 Nm



- High tightening speed
- No reaction forces
- High accuracy
- Reduces user fatigue



CHARACTERISTICS

- Automatic Shut-off
- Brushless motor
- 20 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque
- Speed 90 to 1.000 RPM
- Compact and light weight

CHARACTERISTICS

- Automatic Shut-off
- Brushless motor
- 20 Volt Lithium-Ion battery, choice for 2,5 Ah or 5,0 Ah capacity
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Torque adjustable
- Fine-tuning on hardness of the joint, electronically
- Variable speed control with non-contact trigger
- Run-down speed: 3.200 to 4.500 RPM
- No tightening functionality when battery charge is low

RRI-BA SERIES - ANGLE WRENCHES

Type	Battery voltage	Battery type	Square drive	Bolt capacity mm	RPM	Torque Nm	Weight kg
RRI-BA10S3	20V	Li-Ion 2,5 AH / 5 AH	3/8"	4-5	400-1.000	3-12	1,50
RRI-BA16S3	20V	Li-Ion 2,5 AH / 5 AH	3/8"	5-6	300-600	5-18	1,50
RRI-BA30S3	20V	Li-Ion 2,5 AH / 5 AH	3/8"	6-8	250-450	8-30	1,50
RRI-BA35S3	20V	Li-Ion 2,5 AH / 5 AH	3/8"	6-8	200-350	10-35	1,60
RRI-BA50S3	20V	Li-Ion 2,5 AH / 5 AH	3/8"	6-10	200	22-50	2,00
RRI-BA70S3*	20V	Li-Ion 2,5 AH / 5 AH	3/8"	8-12	160	30-70	2,50
RRI-BA90S4*	20V	Li-Ion 2,5 AH / 5 AH	1/2"	8-12	90	30-90	2,50

Battery and charger to be ordered separately. * Including Reaction Bar

RRI-BIM SERIES - IMPULSE WRENCHES

Type	Square/Hex drive	Torque Nm	RPM	Weight kg
RRI-BIM15AT	1/4" Hex	7-15	4.500	1,16
RRI-BIM15T	3/8" Square	8-15	4.500	1,16
RRI-BIM25AT	1/4" Hex	14-23	4.500	1,18
RRI-BIM25T	3/8" Square	15-25	4.500	1,18
RRI-BIM35T	3/8" Square	22-35	3.500	1,36
RRI-BIM45T	3/8" Square	32-45	3.500	1,42
RRI-BIM65T	1/2" Square	45-65	3.200	1,90

Battery and charger to be ordered separately.

RRI-BS SERIES - SCREWDRIVERS

Type	Volt V	Drive size	Screw size mm	Torque range Nm	RPM	Weight (w/o battery) kg
RRI-BS3H2	20V	1/4" Hex	M3-M4	0,8-3	200-500	0,95
RRI-BS6H2	20V	1/4" Hex	M3-M5	1,5-6	300-1.000	0,95
RRI-BS9H2	20V	1/4" Hex	M3-M5	2-9	300-800	0,95
RRI-BS12H2	20V	1/4" Hex	M4-M6	2,5-12	250-800	0,95

Battery and charger to be ordered separately.

PROGRAMMER



Programmer

FEATURES

- One programmer fits all RRI-B series tools
- Easy to set the tool speed:
 - high speed for metallic assemblies
 - medium speed for plastic assemblies
 - low speed for special assemblies
- Total used time memory function
- Total count memory function
- Operation count memory function
- Tool identification number

All memory functions stored on printed circuit board in the tool.

CHARGER, LI-ION BATTERY, PROGRAMMER, ALUMINIUM COVER, RUBBER PROTECTION COVER & POWER CORD



Charger



Li-Ion battery



Aluminium cover



Rubber Protection Cover for battery



Rubber protection cover



Power cord

Type	Order number
Charger (40 min.)	B84192B
Li-Ion battery 20V 2,5Ah	BB200D-325
Li-Ion battery 20V 5Ah	BB200D-350
Programmer	B74SC180B
Aluminium cover RRI-BIM serie	B10PW15
Rubber protection cover for battery 20V 2,5Ah	33116-B200D-01
Rubber protection cover for battery 20V 5Ah	33116-B200D-02
Rubber protection cover RRI-BIM15T (AT)	C16PW-15
Rubber protection cover RRI-BIM25T (AT)	C16PW-25

Type	Order number
Rubber protection cover RRI-BIM35T	C16PW-25
Rubber protection cover RRI-BIM45T	C16PW-45
Rubber protection cover RRI-BIM65T	C16PW65
Rubber protection cover RRI-BA10S3 / 16S3 / 30S3 / 35S3	C16WR
Rubber protection cover RRI-BA50S3	C16WRB50
Rubber protection cover RRI-BA70S3 / 90S4	C16WRB70
Power cord European style	E86B-VD
Power cord English style	E86B-UK